COUPLING & FITTINGS

CARACTÉRISTIQUES

- CONCEPTION ROBUSTE
- ILS S'ADAPTENT PARFAITEMENT À TOUS LES ÉQUIPEMENTS
- CONFORME À LA NORME ISO22241

Sécurisé, résistant et fiable: la gamme de raccords COUPLING & FITTINGS PIUSI est expressément conçue pour AdBlue® (conforme à la norme ISO22241). Différentes formes et dimensions permettent d'utiliser cette gamme dans toutes les situations.

RACCORDS

DONNÉES TECHNIQUES

HOSETAILS

CODE	DESCRIPTION	TYPE DE LIQUIDES	LONGUEUR	ENTRÉE/SORTIE		TUYAU	PIECES/BOX
			METERS (M)	A	B	Ø (MM)	
F15522000	HOSETAIL M 1" X D.20 PLASTIC	Ad W	-	M 1" BSP	-	20	1
F16435000	HOSETAIL F 1" X D.20 WITH NUT	Ad W	-	F 1" BSP	-	20	1



F15522000



F16435000

COUDES

F15484000	HOSETAIL 90° D.19 F 1" BSP FOR K24 METER	Ad W	-	F 1" BSP	-	19	1
F15450000	HOSETAIL 90° D.19 F ·" BSP	Ad W	-	F 3/4" BSP	-	19	1
F16433000	PIPE FITTING 90° 2/F 1" BSP RING	Ad W	-	F 1" BSP	-	-	1
F15485000	HOSETAIL 90° D.19 1" BSP W/NUT W/NIPPLE	Ad W	-	1" BSP	-	19	1



F15484000



F15450000



F16433000



F15485000

RACCORDS

F16434000	STRAIGHT CONNECTION WITH 2 NUTS F 1" BSP	Ad W	-	F 1" BSP	F 1" BSP	-	1



F16434000

AIR | ANTIGEL | AdBlue® | BIODIESEL | DIESEL | ALIMENTATION | ESSENCE | GRAISSE | KÉROSÈNE | HUILE | EAU | LAVE-GLACE

RACCORDS

DONNÉES TECHNIQUES

CODE	DESCRIPTION	TYPE DE LIQUIDES	LONGUEUR	ENTRÉE/SORTIE		TUYAU	PIECES/BOX
			METERS (M)	A	B	Ø (MM)	

MANCHON

F16073000	SLEEVE F 1" BSP / F 1" BSP (20 PCS) SS	Ad W	-	F 1" BSP	F 1" BSP	-	20
F16458000	SLEEVE F 1" NPT / F 1" BSP (20 PCS) SS	Ad W	-	F 1" NPT	F 1" BSP	-	20



F16073000
F16074000
F16458000

RACCORDS

F15176000	NIPPLE M 1" BSP / M 1" BSP PLASTIC	Ad W	-	M 1" BSP	M 1" BSP	-	1



F15176000

RACCORD ORIENTABLE

F15776000	SWIVEL UNION M 1" BSP / F 1" BSP	Ad W	-	M 1" BSP	F 1" BSP	-	1



F15776000